

D-100™ Hemoglobin Testing System

Specifications

HbA1c Testing for Diabetes

General Specifications

Dimensions

W x D x H.....660 mm x 650 mm x 725 mm
(26 in x 26 in x 29 in)

Weight103 kg (227 lb)

Operating Environment

Temperature.....15 – 35 °C

Humidity.....20 – 80%, non-condensing

Altitude.....3048 m (10,000 ft) max

Heat Generation4092 BTU/h

Power Consumption1200 VA max

Power Input Requirements.....100 – 240 V ~, 50 – 60 Hz

User Interface Integrated LCD touchscreen

Adapter/Ports

- Ethernet on RJ45 port
- RS232 on DB9 port
- External DVI-I connectors (with VGA)
- 6 External USB ports

Liquid Waste Handling

- 2 external waste bottles (5 L each)
- Can be connected to a laboratory drain

Printing Options

- On-screen result review
- Electronic printing to PDF
- External printer (available)

Required Maintenance

- Empty waste bottles (as needed)
- Clean surfaces, touchscreen, and racks (as needed)
- Perform the Clean System procedure (2 minute automated process, every 30,000 tests)

LIS Specifications

- Bi-directional capability with broadcast download of test orders
- Option to add patient demographics to printed results
- LIS result output with option to include comment record
- Chromatogram PDF can be sent automatically to a network folder

Consumable Specifications

D-100™ HbA_{1c} Elution Buffer A

Volume.....2600 mL

Number of Tests > 1100 tests per bottle

Storage Requirements.....15 – 35°C

Onboard Capacity.....2 bottles

D-100™ HbA_{1c} Elution Buffer B

Volume.....1400 mL

Number of Tests > 3000 tests per bottle

Storage Requirements.....15 – 35°C

Onboard Capacity.....2 bottles

D-100™ Wash Solution

Volume.....3300 mL

Number of Tests > 1100 tests per bottle

Storage Requirements.....15 – 35°C

Onboard Capacity.....2 bottles

D-100™ HbA_{1c} Analytical Cartridge

Number of Tests 10,000

Storage Requirements.....2 – 8°C

Onboard Capacity.....1 cartridge

D-100™ HbA_{1c} Calibrator Pack

Calibration Frequency.....once per cartridge

Storage Requirements.....2 – 8°C

D-100™ Prefilters

Number of Tests2,000

Storage Requirements.....2 – 8°C, 120 days at 15 – 35°C

Onboard Capacity.....1 prefilter



BIO-RAD

Sample Handling Specifications

Sample Throughput.....	80 tests/hour
Time to First Result.....	2 minutes, 15 seconds
Sample Analysis Time.....	45 seconds
Sample Preparation.....	None required
Sample Capacity.....	100 samples, continuous loading
Stat Area Sample Capacity.....	3 samples (primary tube or microvial)
Minimum Sample Volume.....	1 mL (13 x 75 mm primary tube)
Specimen Type.....	Whole blood, capillary**
Whole Blood Sample Aspiration Volume.....	9 µL
Prediluted Sample Aspiration Volume.....	495 µL

Acceptable Sample Tube Types

- K2-EDTA
- K3-EDTA
- Potassium Oxalate/Sodium Fluoride
- Sodium Citrate
- Sodium Heparin
- Lithium Heparin

Supported Barcode Symbologies

- Code 39
- Code 128
- Codabar
- Interleaved 2 of 5
- EAN
- UPC

Performance Specifications

Total Precision*.....	≤1.7% CV (NGSP units)
Accuracy.....	Total Error <6%
Linear Range.....	3.5% – 20% HbA _{1c}
Minimum QC Frequency.....	Once per day
Sample Concentration Range.....	50,000 – 350,000 mAU
HbA _{1c} Units Reported.....	IFCC and NGSP

Hemoglobin Interferences

- No interference from hemoglobins S, C, D, or E
- No interference from fetal hemoglobin up to 30%
- No interference from labile HbA_{1c}
- No interference from carbamylated hemoglobin

* Total precision is based on a 3-instrument, 60-day precision study using 3 lots of reagents to generate a total of 720 data points per sample. It includes the following sources of variation: within-run (repeatability), between-run, between-day, between-instrument, and between-lot.

** Not available in US for the capillary collection kit.



**Bio-Rad
Laboratories, Inc.**

For further information, please contact the Bio-Rad office nearest you or visit our website at www.bio-rad.com/diagnostics

Clinical
Diagnostics Group

Web site www.bio-rad.com/diagnostics USA 1 800 224 6723 Australia 61 2 9914 2800 Austria 43 1 877 8901 Belgium 32 03 710 53 00
 Brazil 55 31 3689 6600 Canada 1 514 334 4372 China 86 21 61698500 Czech Republic 420 241 430 532 Denmark 45 4452 1000 Finland 358 9 804 22 00
 France 33 1 47 95 60 00 Germany 49 0 89 318 840 Greece 30 210 7774396 Hong Kong 852 2789 3300 Hungary 36 1 459 6100 India 1800 180 1224
 Israel 972 3 9636050 Italy 39 02 216091 Japan 81 3 6361 7070 Korea 82 2 3473 4460 Mexico 52 55 5488 7670 The Netherlands 31 318 540666
 New Zealand 64 9 415 2280 Norway 47 23 38 41 30 Poland 48 22 3319999 Portugal 351 21 472-7700 Russia 7 495 721 1404 Singapore 65 6415 3170
 South Africa 27 11 442 85 08 Spain 34 91 590 5200 Sweden 46 8 555 127 00 Switzerland 41 0 26 674 55 05 06 Taiwan 886 2 2578 7189
 Thailand 662 651 8311 United Kingdom 44 0 20 8328 2000